



L-Series High-density Optical Fiber Patch Panel, 3U

Description

Vericom L-Series high density optical fiber patch panels are used for data network communication, data center, servers and switch connectivity. It can be applied to 10G, 40G and 100G networks by featuring large operating space and flexible module configurations.

Features & Benefits

- Up to 96 cores per U with MPO-LC modules
- 12-core, 24-core MPO to LC, and MPO to MPO available
- Fully-enclosed internal cable management
- Snap- in design for easy operation
- Removable front cable manager
- Up to 288 Core LC

Compliance & Standards

- ISO/IEC 11801-5
- ISO/IEC 24764
- ANSI/TIA-942-A/B
- EN 50173-5

Product Specifications

Rack Height	3U	
Installation	19" Standard Rack	
Dimension (Width x Depth x Height)	482.6X339X132mm	
Weight	7kg	
Material	Frame	Cold Rolled Plate With Powder Coating
	Other Components	PC/ABS
Capacity	Up to 12 Modules	
Density	Maximum 288-core LC	
Operating Temperature (°C)	-25~60	

Drawing



Applications

- Data Center
- Telecommunication Infrastructure



## L-Series High-density Optical Fiber Patch Panel, 3U

## Ordering Information

Part No.	Product Name	Description
VR-F-MPO-3U	L-Series Optical Fiber Patch Panel	3U, Module Unloaded