

## Cabinet Air Cooling ESS VE-215



### Features



#### SAFE AND RELIABLE

- Approved industry certification of Cell pass test by UL/IEC
- Multi-level design for fire control
- Built-in early warning detection system
- IP 54 rating for enclosure
- IP66 for battery pack



#### ENHANCED MONITORING CONTROL

- Integrated performance control for local and remote monitoring.
- Data logging for component level status monitoring.
- Real-time system operation analysis on terminal screen.



#### EFFICIENT AND DURABLE

- Modular battery and cooling equipment are designed for better temperature control



#### SMART AND SCALABLE

- Modular design supports ease of installation, expansion, and maintenance
- ESS self-diagnosis and healing function
- Supports remote maintenance and upgrades

TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Battery Parameters	
Cell Type	LFP 3.2V/280Ah
Configuration	1P240S
Nominal Capacity	215kWh
Nominal Voltage	768 Vdc
Voltage Range	600~876 V
BMS Communication Interface	RS485, CAN, Ethernet
Standard & Certification	IEC/EN 62619, IEC/EN 63056, IEC/EN 62477-1, IEC/EN 60730-1, EN 61000-6-1/-2/-3/-4, RoHS 2.0, UL 1973, UL 9540A, UL 60730-1
AC Parameters	
AC Nominal Power	100 kVA
THDi	<3%(rated power)
DC Component	<0.5%
AC Nominal Voltage	400 Vac
Grid Voltage Range	400V, 3W+N+PE
Power Factor	>0.99
Adjustable Power Factor	-1(leading)~+1(lagging)
Operating Grid Frequency	50 Hz
Grid Frequency Range	± 5 Hz
Isolation Type	Non-isolated
Protection Function	Anti-Islanding protection, AC overcurrent protection, AC surge protection, Insulation impedance detection
Standard & Certification	IEC 61000-6-2, IEC 61000-6-4
Basic Parameters	
Enclosure Dimensions (W*H*D)	1,650*2,500*1,250mm
Weight	~3 T
Enclosure IP Rating	IP54
Battery Pack IP Rating	IP66
Operating Temperature	-30℃~+50℃
Relative Humidity	5%~ 95%, non-condensing
Max. Altitude (above sea level)	3000 m
Battery Cooling Mode	Air cooling
Cooling Mode	Intelligent forced air cooling+ roof-top air conditioning system
Fire Suppression System	Aerosol, pack-level FSS
Communication Protocol	Modbus TCP, Modbus RTU, CAN2.0

TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.