



Optical Fiber Patch Panel with Splitter, Fully Loaded

Features & Benefits

- Fast and easy front access to all splitter ports
- Bi-directional performance with accurate splitting ratios
- Ultra-broadband range (1260-1650 nm)
- Low Insertion Loss
- Excellent uniformity
- Low Polarization Dependent Loss (PDL)
- Solid steel construction from powder coated CRCA
- Integrated fiber management accessories
- 2011/65/EU RoHS compliant and halogen free
- Low Polarization Dependent Loss (PDL)


Compliance & Standards

- ISO/IEC 11801
- TIA/EIA-526-7
- ANSI/TIA-568-C.3
- ITUG.657
- TIA-598-C
- GR-1209
- GR-1221
- EN 50173: 2002

Drawing



Technical Drawing



TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

REV.20200901.1



Optical Fiber Patch Panel with Splitter, Fully Loaded

Product Specifications

| | | | | | | | | |
|----------------------------------|-----------------|-------|-------|-------|------|-------|-------|-------|
| Material | SPCC/Plastic | | | | | | | |
| Surface | Spray | | | | | | | |
| Connector Type | SC/LC (UPC/APC) | | | | | | | |
| Operating Wave length | 1260-1650 nm | | | | | | | |
| Parameter | 1x4 | 1x8 | 1x16 | 1x32 | 2x4 | 2x8 | 2x16 | 2x32 |
| Insertion Loss (dB) | ≤8.0 | ≤11.1 | ≤14.1 | ≤17.4 | ≤8.2 | ≤11.4 | ≤14.4 | ≤17.7 |
| Channel Uniformity (dB) | ≤0.7 | ≤1.0 | ≤1.2 | ≤1.5 | ≤0.7 | ≤1.0 | ≤1.2 | ≤1.5 |
| Polarization Dependent Loss (dB) | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.3 |
| Wavelength Dependent Loss (dB) | 0.3 | 0.3 | 0.3 | 0.3 | 0.3 | 0.3 | 0.3 | 0.3 |
| Connector Loss (dB) | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 |
| Return Loss (dB) | ≥55 | | | | | | | |
| Directivity (dB) | ≥55 | | | | | | | |
| Operating Temperature (°C) | -40~70 | | | | | | | |
| Maximum Input Power (mV) | 500 | | | | | | | |

Ordering Information

| Part No. | Product Name | Description |
|------------|--|---------------------|
| PLCBxxxxyz | Optical Fiber Splitter Patch Panel, Fully Loaded | xxx Splitting Ratio |

xxx=Split Ratio (104=1:4, 108=1:8....., 232=2:32)

y=Fiber Type (S2=G.652D, A1=G.657A1, A2= G.657A2)

x=Connector Type: (1=SC, 2=LC)

z=Connector Precision: (U=UPC, A=APC)