



MPO Adaptor Plate, L-Series

Description

The MPO adaptor plates are used to connect pre-terminated backbone optical fibers and patch cord, and offer a fast "plug and play" way instead of the splicing modules. In the MTP/MPO multimode applications, the patching modules are facilitating "end to end" paralleled optical fiber cable connections with 8 cores, 12 cores or 24 cores.

Features & Benefits

- 6 adaptors per module (LC or MTP/MPO adaptor)
- Fast and toolless installation
- Rear cable holder
- SM, OM3, OM4, OM5 fiber available
- High performance LC adaptors with color identification
- Different colors of adaptors shell

Compliance & Standards

- ISO/IEC 24764
- ISO/IEC 11801-5
- ANSI/TIA-942-A/B
- EN50173-5

Drawing



Applications

- Data Center
- Telecommunication Infrastructure



MPO Adaptor Plate, L-Series

Product Specifications

Application	L-series Optical Fiber Patch Panel	
Material	PC/ABS	
Color	Black	
Adaptor Color	LC Single Mode	Yellow
	LC OM3	Aqua
	LC OM4	Violet
	LC OM5	Lemon Green
	MPO	Black
Ferrule Material	LC: Zirconia Ceramic; MTP/MPO: Composite Material	
Operating Temperature (°C)	-10-60	
Durability	MPO ≥100 times	
	LC ≥1000 times	

Ordering Information

Part No.	Product Name	Description
VR-F-MPO-MD1	L-Series Blank Plate	L-Series Blank Plate
VR-F-MPO-MD2SM-12	L-Series LC Adaptor Plate	12 Cores, Single Mode
VR-F-MPO-MD2OM3-12	L-Series LC Adaptor Plate	12 Cores, OM3
VR-F-MPO-MD2OM4-12	L-Series LC Adaptor Plate	12 Cores, OM4
VR-F-MPO-MD2OM5-12	L-Series LC Adaptor Plate	12 Cores, OM5
VR-F-MPO-MD2SM-24	L-Series LC Adaptor Plate	24 Cores, Single Mode
VR-F-MPO-MD2OM3-24	L-Series LC Adaptor Plate	24 Cores, OM3
VR-F-MPO-MD2OM4-24	L-Series LC Adaptor Plate	24 Cores, OM4
VR-F-MPO-MD2OM5-24	L-Series LC Adaptor Plate	24 Cores, OM5
VR-F-MPO-MD2B	L-Series MPO Adaptor Plate	6 Ports, 12 Cores, Black
VR-F-MPO-MD2R	L-Series MPO Adaptor Plate	6 Ports, 12 Cores, Red
VR-F-MPO-PJ01-24	L-Series Splicing Accessory	24 Cores
VR-F-MPO-PJ01-48	L-Series Splicing Accessory	48 Cores